




## Data sheet

Commercial Art.No.: 80.020.6003.0

Solid state reversing relay CEMOS-SSPHC-400V-2,5A

ceмос electronic controlled reversing contactor, in A closed housing, dimensions (B x H x T) 45 x 75 x 110 mm control voltage: 24 V DC +10%/-15% output data: 400 VAC / 2,5A motor power: 0,75 kW



Commercial Art.No.	80.020.6003.0
EAN	4015573448254
Order Unit	1

## Technical data

### General

Number of phases	3
Modular version	No

### Technical data

Connection type	screw connection
Type of excitation	AC/DC
Min. connection voltage	100 V
Max. connection voltage	500 V
Min. control voltage frequency	50 Hz
Max. control voltage frequency	60 Hz
Rated operating current AC-1	2.5 A
Min. control voltage	24 V

### Dimensions

Depth	110 mm
Width	45 mm
Height	75 mm

### Classification

ECLASS 11	
ECLASS 8.1	27371014
ETIM 7.0	EC002055
ETIM 6.0	EC002055
ETIM 5.0	EC002055
ETIM 4.0	EC002055
ETIM 3.0	EC002055

### Product compliance

ROHS conformity status	Compliant/Exempted
ROHS exceptions	III-6(c)
REACH-SVHC conformity status	Duty-To-Declare
REACH-SVHC substances	Hexahydromethylphthalic-anhydride; Lead
REACH-SVHC CAS numbers	25550-51-0; 7439-92-1