



Model: LP383450		Overcharge Detection Voltage(V)	4.28±0.05
Battery pack specification (电芯组规格)	Min.Capacity 最低容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)	Overdischarge Detection Voltage(V)	3.0±0.1
	Typical Capacity 典型容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)	过放保护电压 (V)	Limited to Max loading current 仅用于最大的负载电流
	Nominal Voltage 标称电压 (V)	峰值 (A)	constant (A) 持续 1.0 (A)
Internal impedance 内阻 (≤) (mΩ, AC 1KHz)	3.7	Customer required Max loading current 客户要求最大的负载电流	constant (A) 持续 1.0 (A)
Ambient Conditions (环境温度)	Charge Temp. 充电温度 (°C)	If actual application loading current is bigger than EEMB suggested, please indicate. The application profile is important for an appropriate PCM design. (如实际应用的负载电流大于EEMB提供值, 请提出来, 实际的应用情况对PCM的设计至关重要)	
	Discharge Temp. 放电温度 (°C)	峰值 1.5 (A)	
	Humidity (湿度)	持续 1.0 (A)	

**Battery protection
Related Value:
(相关的电芯保护值)**

Remark(备注):	1. No scratch, discoloration, discoloration and leakage on the appearance of the cell/电芯表面无划痕、变形、污点及漏液等现象).
	2. Rohs compliant(严格按照ROHS要求生产).

		Drawn:	Gongjili	Revise No.:	E4-2009
		Checked 1:	Cella	Projection:	
Title		Checked 2:		Page:	1/1
File NO.		Approved:		Scale:	1:1
A07439		Draw Date:	2012/12/28	Unit:	mm