

PRODUCT DETAILS

Model	Voltage (V)	Current (A)	Power (W)	Air Volum (CFM)	Speed (Rpm)	Noise Level (db)	Weight (G)
RQD6015LS	5	0.20	1.00	12.00	3500	27.2	39
RQD6015MS	5	0.25	1.25	14.20	3900	28.8	39
RQD6015HS	5	0.37	1.85	16.6	4500	32.4	39
RQD6015LS	12	0.09	1.08	12.00	3600	27.2	39
RQD6015MS	12	0.11	1.32	14.20	3900	28.8	39
RQD6015HS	12	0.13	1.56	16.60	4500	32.4	39
RQD6015LS	24	0.07	1.68	14.20	3900	28.8	39
RQD6015MS	24	0.08	1.92	15.50	4200	30.8	39
RQD6015HS	24	0.09	2.16	16.20	4500	32.4	39

General description of the:

Each of the fans has DC brushless motor for driving, a tubular frame and plastic impeller. they have some superior features such as large air volume, low noise ,low EMI, low power consumption, high efficiency and long life etc. they are specially used in computer system. office automation products, and automatic applications on the ground for air cooling and venting where there is a DC power supply.

Application cond itions:

Temperature Range(°C):-20°C+60°CBall Bearing(B) -20°C+40°C Sleeve Bearing(S);

Humidity permissible(%):≤90%(25°C);

Atmospheric Pressure 55kpa;

Vibration Permissible: Frequency 10Hz,Double Amplitude 1.5mm;

Impact Permissible: (peak acceleration)40m/ S²

ILLustration Of The Code:

