Note: This datasheet may be out of date.
Please download the latest datasheet of BLM18BB221SN1# from the official website of Murata Manufacturing

Co., Ltd.

https://www.murata.com/en-eu/products/productdetail?partno=BLM18BB221SN1%23

BLM18BB221SN1#

"#" indicates a package specification code.







< List of part numbers with package codes >

BLM18BB221SN1B BLM18BB221SN1D BLM18BB221SN1J



Appearance & Shape







The chip ferrite beads BLM series is designed to work nearly as a resistor at noise frequencies, which greatly reduces the possibility of resonance and leaves signal wave forms undistorted.
BLM series is effective in circuits without stable ground lines because BLM series does not need a connection to ground.

BLM_B series can minimize attenuation of the signal waveform due to its sharp impedance characteristics. Various impedances are available to match signal frequency.

The nickel barrier structure of the external electrodes provides excellent solder heat resistance.



Other Usage For general



Packaging Information

Packaging	Specifications	Minimum Order Quantity
В	Bulk(Bag)	1000
D	180mm Paper Tape	4000
J	330mm Paper Tape	10000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Note: This datasheet may be out of date

 $\underline{ Please \ download \ the \ latest \ data sheet \ of \ BLM18BB221SN1\# \ from \ the \ of ficial \ website \ of \ Murata \ Manufacturing}$

Co., Ltd. https://www.murata.com/en-eu/products/productdetail?partno=BLM18BB221SN1%23

BLM18BB221SN1#

"#" indicates a package specification code.



Shape	SMD
Size Code (in mm)	1608
Size Code (in inch)	0603
Length	1.6mm
Length Tolerance	±0.15mm
Width	0.8mm
Width Tolerance	±0.15mm
Thickness	0.8mm
Thickness Tolerance	±0.15mm
Impedance (at 100MHz)	220Ω
Impedance (at 100MHz) Tolerance	±25%
Rated Current (at 85°C)	450mA
Rated Current (at 125°C)	450mA
DC Resistance(max.)	0.45Ω
Operating Temperature Range	-55°C to 125°C
Mass(typ.)	0.005g
Number of Circuit	1

2 of 3

Attention

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

^{1.} This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.


Note: This datasheet may be out of date $\underline{ Please \ download \ the \ latest \ data sheet \ of \ BLM18BB221SN1\# \ from \ the \ of ficial \ website \ of \ Murata \ Manufacturing}$


Co., Ltd. https://www.murata.com/en-eu/products/productdetail?partno=BLM18BB221SN1%23

BLM18BB221SN1#

"#" indicates a package specification code.







Impedance-Frequency Characteristics

Equivalent Circuit

3 of 3

Attention

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



^{1.} This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.