

PRODUCT DETAILS

| Model | Voltage (V) | Current (A) | Power (W) | Air Volum (CFM) | Speed (Rpm) | Noise Level (db) | Weight (G) |
|-----------|-------------|-------------|-----------|-----------------|-------------|------------------|------------|
| RQD4010LS | 5 | 0.08 | 0.40 | 4.70 | 4200 | 14.0 | 14 |
| RQD4010MS | 5 | 0.11 | 0.55 | 5.70 | 4800 | 20.0 | 14 |
| RQD4010HS | 5 | 0.19 | 0.95 | 6.70 | 6000 | 25.0 | 14 |
| RQD4010LS | 12 | 0.07 | 0.84 | 4.70 | 4200 | 14.0 | 14 |
| RQD4010MS | 12 | 0.08 | 0.96 | 5.70 | 4800 | 20.0 | 14 |
| RQD4010HS | 12 | 0.10 | 1.20 | 6.70 | 6000 | 25.0 | 14 |
| RQD4010LS | 24 | 0.07 | 1.68 | 4.70 | 4200 | 14.0 | 14 |
| RQD4010MS | 24 | 0.08 | 1.92 | 5.70 | 4800 | 20.0 | 14 |
| RQD4010HS | 24 | 0.09 | 2.16 | 6.70 | 6000 | 25.0 | 14 |

General description of the:

Each of the fans has DC brushless motor for driving, a tubular frame and plastic impeller. they have some superior features such as large air volume, low noise ,low EMI, low power consumption, high efficiency and long life etc. they are specially used in computer system. office automation products, and automatic applications on the ground for air cooling and venting where there is a DC power supply.

Application cond itions:

Temperature Range(°C):-20°C+60°CBall Bearing(B) -20°C+40°C Sleeve Bearing(S);

Humidity permissible(%):≤90%(25°C);

Atmospheric Pressure 55kpa;

Vibration Permissible: Frequency 10Hz,Double Amplitude 1.5mm;

Impact Permissible: (peak acceleration)40m/ S²

ILLustration Of The Code:

