








# ITEM:2.54 MM IDC series



**Material:**  
 Insulator: PBT  
 Contact: Brass  
 Contact Plated: Nickel Plated  
**Specification:**  
 Current Rating: 1 Amp.  
 Withstanding Voltage: AC 500V for 1 Minute.  
 Insulation Resistance: 100M  $\Omega$  Max. at DC 500V.  
 Contact Resistance: 1  $\Omega$  Min.  
 Operating Temperature: -20°C ~ +105°C.

Pos.	Dim. A	Dim. B	Dim. C	Dim. D
6	12.32	6.35	5.08	12.12
8	14.86	8.89	7.62	14.66
10	17.40	11.43	10.16	17.20
12	19.94	13.97	12.70	19.74
14	22.48	16.51	15.24	22.28
16	25.02	19.05	17.78	24.82
18	27.56	21.59	20.32	27.36
20	30.10	24.13	22.86	29.90
22	32.64	26.67	25.40	32.44
24	35.18	29.21	27.94	34.98
26	37.72	31.75	30.48	37.52
30	42.80	36.83	35.56	42.80
34	47.88	41.91	40.64	47.68
36	50.42	44.45	43.18	50.22
40	55.50	49.53	48.26	55.60
44	60.58	54.61	53.34	60.38
50	68.20	62.23	60.96	68.40
60	80.90	74.93	73.66	80.70
64	85.98	80.01	78.74	85.78