Data Brief



SiI9185A 3:1 HDMI Switch

Data Brief

Document # SiI-DB-1016-C01

June 2010

Copyright Notice

Copyright © 2008-2010 Silicon Image, Inc. All rights reserved. These materials contain proprietary and confidential information (including trade secrets, copyright and other interests) of Silicon Image, Inc. You may not use these materials except only for your bona fide non-commercial evaluation of your potential purchase of products and/or services from Silicon Image or its affiliates, and/or only in connection with your purchase of products and/or services from Silicon Image or its affiliates, and only in accordance with the terms and conditions herein. You have no right to copy, modify, transfer, sublicense, publicly display, create derivative works of or distribute these materials, or otherwise make these materials available, in whole or in part, to any third party.

Patents

The subject matter described herein contains one or more inventions claimed in patents and / or patents pending owned by Silicon Image, Inc., including but not limited to the inventions claimed in US patents #6,914,637, #6,151,334, #6,026,124, #5,974,464 and #5,825,824.

Trademark Acknowledgment

Silicon ImageTM, VastLaneTM, SteelVineTM, PinnaClearTM, SimplayTM, Simplay HDTM, SatalinkTM, and TMDSTM are trademarks or registered trademarks of Silicon Image, Inc. in the United States and other countries. HDMITM, the HDMI logo and High-Definition Multimedia InterfaceTM are trademarks or registered trademarks of, and are used under license from, HDMI Licensing, LLC.

Export Controlled Document

This document contains information subject to the Export Administration Regulations (EAR) and has a classification of EAR99 or is controlled for Anti-Terrorism (AT) purposes. Transfer of this information by any means to an EAR Country Group E:1 or foreign national thereof (whether in the U.S. or abroad) may require an export license or other approval from the U.S. Department of Commerce. For more information, contact the Silicon Image Director of Global Trade Compliance.

Further Information

To request other materials, detailed hardware and software guides, and additional information, contact your local Silicon Image, Inc. sales office or visit the Silicon Image, Inc. web site at <u>www.siliconimage.com</u>. Information about obtaining licenses required for using HDMI and HDCP technologies is available from <u>www.hdmi.org</u> and <u>www.digital-cp.com</u>.

© 2008-2010 Silicon Image, Inc. All rights reserved



General Description

The SiI9185A 3:1 HDMI Switch is the first generation of TMDSTM switching devices that supports the features of revision 1.3 of the HDMI[®] Specification and integrates the latest generation of TMDS core technology. With three HDMI inputs and a single output, the switch provides a low-cost method of retransmitting protected digital audio and video and adding additional HDMI ports to the latest digital TVs (DTVs), giving consumers a truly all-digital experience. New DTVs can easily connect to the many HDMI sources coming to market, including DVDs, Set Top Boxes (STBs), game consoles, PCs, camcorders, and digital still cameras.

Unlike some other HDMI switching devices, which use high-speed analog switches that can degrade TMDS signals, the SiI9185A switch uses TMDS cores to recover and retransmit the HDMI signal.

Backward compatibility with DVI 1.0 allows HDMI systems to connect to any DVI 1.0 source.

The SiI9185A switch is the first generation of devices from Silicon Image that integrates Extended Display Identification Data (EDID). The EDID is stored in onboard RAM downloaded from the system microcontroller during power-up or initialization. The EDID is reflected on each of the three HDMI ports through the DDC bus. The device also allows using EDID stored on an external ROM, and either location can be selected for each port. Having the flexibility to provide EDID content from on-board RAM can eliminate up to three EDID ROMs and save board space.

This device provides additional features that eliminate external components, lower system cost, and provide enhanced features to the end-user. The switch provides a complete solution for switching sink-side HDMI signals, such as DDC switching and Hot Plug Detect (HPD) control for each port, and 5-volt sense to speed audio mute when changing HDMI cables. For sourceside applications, DDC switching can be bypassed with an external 4-channel I²C bus switch to allow clock stretching.

TMDS

- The TMDS cores are capable of receiving and transmitting at 2.25 Gbps.
- Video resolutions up to 1080p, 60 Hz, 12-bit or 720p/1080i, 120 Hz, 12-bit are supported.
- An adaptive equalizer provides long cable support, even at Deep Color resolutions.
- The transmitter includes pre-emphasis.

CEC Support

- An integrated HDMI-compliant CEC I/O and the Silicon Image CEC API eliminate the need for additional external components.
- The API manages all CEC signaling using the CEC protocol and makes CEC information available to the system microcontroller, eliminating the microcontroller overhead needed to manage the CEC bus and thus simplifying design.

Control Capability

- The device can be controlled by the local I^2C bus.
- An optional stand-alone mode (for which I²C control is not required) is available for speeds up to 165 MHz and allows the device to act as a simple switcher.
- The CEC and EDID are still functional during the very-low-power standby mode when the DTV is off, which meets Energy Star and other power-saving requirements.

Package

• 80-pin, 12 mm by 12 mm, 0.5 mm pitch, TQFP package




Figure 1. Typical Application

SiI9185A Pin Mapping

Figure 2 shows the pin diagram for the SiI9185A switch in the 80 pin, 12 mm by 12 mm, 0.5 mm pitch, TQFP package. Pin names are generalized by type for this document. The list below the diagram describes the purpose of each type.





Figure 2. Pin Mapping

Package Information

These drawings are not to scale.

Package Dimensions



TOP VIEW

- NOTE:
- \bigwedge To be determined at seating plane \bigwedge Dimensions D₁ and E₁ do not include mold protrusion. E₁ and E₁ are
- maximum plastic body size dimensions including mold mismatch.
- A Dimension b does not include Dambar protrusion. Dambar cannot be located on the lower radius of the foot.
- Exact shape of each corner is optional.
 These dimensions apply to the flat section of the lead between 0.10 mm and 0.25 mm from the lead tip.
- \underline{A}_1 is defined as the distance from the seating plane to the lowest point of the package body.
- 7 Controlling dimension: millimeter.
- 8 Reference document: JEDEC MS-026-ADE
- 9 Special characteristics C Class: ccc

Symbol	Description	Min	Тур	Max
А	Thickness			1.20
A_1	Stand-off	0.05	—	0.15
A_2	Body Thickness	0.95	1.00	1.05
b	Plated Lead Width	0.17	0.20	0.27
b_1	Metal Lead Width	0.17	0.20	0.23
с	Plated Lead Thickness	0.09		0.20
c_1	Metal Lead Thickness	0.09		0.16
D	Footprint	1	4.00 BS0	5
D ₁	Body Size	1	2.00 BSC	2
Е	Footprint	1	4.00 BSC	2
E_1	Body Size	12.00 BSC		
e	Lead Pitch		0.50 BSC	1
L	Lead Foot Length	0.45	0.60	0.75
L_1	Total Lead Length		1.00 REF	7
R_1	Lead Radius, Inside	0.08	0.15	_
R ₂	Lead Radius, Outside	0.15	0.20	0.25
S	Lead Horizontal Run	0.20	_	
θ	Lead Foot Angle	0°	3.5°	7°
θ_1	Vertical Lead Angle	0°		
θ_2	Upper Facet Angle	11°	12°	13°
θ_3	Lower Facet Angle	11°	12°	13°

Dimensions in millimeters.

Overall thickness A = A1 + A2.





Figure 3. 12.0 mm x 12.0 mm TQFP Package Diagram

Marking Specification



Legend	Description	
LLLLL.LLLL	Lot number	
YY	Year of manufacture	
WW	Week of manufacture	
TTTTTT	Trace code	
М	Maturity code	

The universal package can be used in lead-free and ordinary process lines.

Figure 4. Marking Diagram

Ordering Information

Production Part Numbers:

Device	Part Number	
Standard	SiI9185ACTU	

Disclaimers

These materials are provided on an "AS IS" basis. Silicon Image, Inc. and its affiliates disclaim all representations and warranties (express, implied, statutory or otherwise), including but not limited to: (i) all implied warranties of merchantability, fitness for a particular purpose, and/or non-infringement of third party rights; (ii) all warranties arising out of course-of-dealing, usage, and/or trade; and (iii) all warranties that the information or results provided in, or that may be obtained from use of, the materials are accurate, reliable, complete, up-to-date, or produce specific outcomes. Silicon Image, Inc. and its affiliates assume no liability or responsibility for any errors or omissions in these materials, makes no commitment or warranty to correct any such errors or omissions or update or keep current the information contained in these materials, and expressly disclaims all direct, indirect, special, incidental, consequential, reliance and punitive damages, including WITHOUT LIMITATION any loss of profits arising out of your access to, use or interpretation of, or actions taken or not taken based on the content of these materials.

Silicon Image, Inc. and its affiliates reserve the right, without notice, to periodically modify the information in these materials, and to add to, delete, and/or change any of this information.

Notwithstanding the foregoing, these materials shall not, in the absence of authorization under U.S. and local law and regulations, as required, be used by or exported or re-exported to (i) any U.S. sanctioned or embargoed country, or to nationals or residents of such countries; or (ii) any person, entity, organization or other party identified on the U.S. Department of Commerce's Denied Persons or Entity List, the U.S. Department of Treasury's Specially Designated Nationals or Blocked Persons List, or the Department of State's Debarred Parties List, as published and revised from time to time; (iii) any party engaged in nuclear, chemical/biological weapons or missile proliferation activities; or (iv) any party for use in the design, development, or production of rocket systems or unmanned air vehicles.

Products and Services

The products and services described in these materials, and any other information, services, designs, know-how and/or products provided by Silicon Image, Inc. and/or its affiliates are provided on as "AS IS" basis, except to the extent that Silicon Image, Inc. and/or its affiliates provides an applicable written limited warranty in its standard form license agreements, standard Terms and Conditions of Sale and Service or its other applicable standard form agreements, in which case such limited warranty shall apply and shall govern in lieu of all other warranties (express, statutory, or implied). EXCEPT FOR SUCH LIMITED WARRANTY, SILICON IMAGE, INC. AND ITS AFFILIATES DISCLAIM ALL REPRESENTATIONS AND WARRANTIES (EXPRESS, IMPLIED, STATUTORY OR OTHERWISE), REGARDING THE INFORMATION, SERVICES, DESIGNS, KNOW-HOW AND PRODUCTS PROVIDED BY SILICON IMAGE, INC. AND/OR ITS AFFILIATES, INCLUDING BUT NOT LIMITED TO, ALL IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND/OR NON-INFRINGEMENT OF THIRD PARTY RIGHTS. YOU ACKNOWLEDGE AND AGREE THAT SUCH INFORMATION, SERVICES, DESIGNS, KNOW-HOW AND PRODUCTS HAVE NOT BEEN DESIGNED, TESTED, OR MANUFACTURED FOR USE OR RESALE IN SYSTEMS WHERE THE FAILURE. MALFUNCTION, OR ANY INACCURACY OF THESE ITEMS CARRIES A RISK OF DEATH OR SERIOUS BODILY INJURY, INCLUDING, BUT NOT LIMITED TO, USE IN NUCLEAR FACILITIES, AIRCRAFT NAVIGATION OR COMMUNICATION, EMERGENCY SYSTEMS, OR OTHER SYSTEMS WITH A SIMILAR DEGREE OF POTENTIAL HAZARD. NO PERSON IS AUTHORIZED TO MAKE ANY OTHER WARRANTY OR REPRESENTATION CONCERNING THE PERFORMANCE OF THE INFORMATION. PRODUCTS. KNOW-HOW, DESIGNS OR SERVICES OTHER THAN AS PROVIDED IN THESE TERMS AND CONDITIONS.



1060 E. Arques Avenue Sunnyvale, CA 94085 T 408.616.4000 F 408.830.9530 www.siliconimage.com